

## PERFORATED VINYL S/A ONE WAY VISION OWMVXK1819040

## Application

- Window Graphic
- Vehicle Graphic
- Signs & ADs

## Technical Data Sheet

Item Code		OWMVXK1819040
PVC Face Film	Type	Monomeric PVC film
	Caliper (um)	180
	Open Rate	40%
Glue	Type	Clear removable solvent based acrylic glue
	Thickness ( um )	25
	180° Peeling Force(N/in)	≥5.2N
	Holding Power	≥ 48Hours
Liner Paper	Type	Laninated wood-free paper
	Weight (gsm)	190
Available size	Width	0.914/1.06/1.27/1.37/1.52m (36"/42"/50"/54"/60")
	Length	50m/45.72m (164'/150')
Shelf Time (Month) (20°C x 50% R.H)		12 Months
Applying Temperature Range °C		-10~65°C
Outdoor durability		12 Months

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

## Ink Printability

SOLVENT



ECO-SOLVENT



UV

LATEX

SCREEN PRINTING



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,  
Haining, Zhejiang, China  
Tel: +86-573-80776996 Fax: +86-573-80776998  
Mob/Skype/Wechat/WhatsApp: +86-158-5832-2153  
mailto:contact@hncmax.com

